

EPC-406 Converter



Features

EPC-406 USB to RS-422/485 Converter

- Standard USB2.0 compliant.
- Serial transmission speed of 300-115.2Kbps.
- Supports RS-422/485 communication interface.
- Runs in Windows 95/98/2000/XP/Vista/Vista x64/7.
- Operates at -10°C to 60°C with relative humidity of 20%-95%.
- USB self powered, no additional power adaptor or battery required.
- With optical isolation protection. (2.5KVrms / 500VDC isolation voltage)
- Built-in surge protection on power input and +/-15KV ESD protection for RS-485.

Ordering Information

Package Content:

- EPC-406 x 1
- Cable x 1
- Quick Start Guide x 1
- USB Driver CD (EPC-406)

Optional Accessories:

- AC-DC Adapter

Specifications

Model No.	EPC-406
Power Input	USB powered
Comm. Baudrate	300-115.2 Kbps
Power Consumption	-
Operating Temp.	-10°C - 60°C / 14°F ~ 140°F
Relative Humidity	20%-95%
Dimension (mm)	95 x 62 x 28 (LxWxH)
Weight (Device)	70g ±5%

BF-430 TCP/IP Converter



Features

- CE / FCC approved.
- Provide IP Setup Utility.
- High speed 10/100M TCP/IP Converter.
- Simple & friendly GUI interface software utility.
- Watchdog function ensures system free for halting.
- Conversion of RS-232 and RS-485 to fast Ethernet data transmission.
- Provide network ability for Access Control and Time Attendance System.

Specifications

Model No.	BF-430
CPU	16-bit RISC
RAM	2 MB (1M x 16bits)
ROM	128KB
Interface	LAN: RJ-45 Connector COM: RS-232 / RS-485
Power Input	DC 9V, 500mA (max)
Power Consumption	4.5W (max)
Comm. Baudrate	300bps~115.2Kbps-N-8-1
Operating Temp.	0° C~50° C / 32° F~122° F
Relative Humidity	5%~95% (Non Condensing)
Dimension(mm)	97 x 75 x 27 LxWxH
Weight (Device)	165g +/- 5%

Ordering Information

Package Content:

- BF-430 x 1
- Software CD x 1

Optional Accessories:

- AC-DC Adapter