

PXR-70 EM Metal Reader



Features

- Supports EM (125 KHz) card.
- Metal casing to have the great anti-impact capability
- Mullion type reader , suitable for being installed on narrow door frame
- Provides RS-485 communication interface for long distance installation.(PXR-70ES)
- Wide operation temperature range; It can be installed in extreme cold or hot regions
- Case sensor detection function.
- Watchdog function secures system free from halting.

Ordering Information

Package Content:

- PXR-70 x 1
- Accessory Pack x 1
- Quick Start Guide x 1
- Plate x 1

Model No. Identification

P X R - 7 0 E T

T: T2 / W: Wiegand
S: RS-485
E: EM / M: MIFARE®
Device Type
Product Category

Color

●
Gold
(Go)

Specifications

Model No.	PXR-70ET	PXR-70EW	PXR-70ES
Read Format	EM (125 KHz)		
Read Range	2 cm(max)		
Comm. Interface	T2	Wiegand	RS-485
Input Port	Case Sensor x 1		
ID Setting	None		DIP switch setting
Comm. Baudrate	None		19,200 bps-N-8-1
LED Indicator	Power / Comm.		
Beep Tone	Buzzer		
Power Input	DC 12V / 1A		
Current Consumption	200mA (max)		
Operating Temp.	-10°C~ 70°C / 14°F~ 158°F		
Relative Humidity	20% ~ 80%(Non-condensing)		
Dimension (LxWxH)(mm)	146 x 42 x 24		