

PXR-92 EM Reader



Features

- Support 125 KHz-EM card
- Reading distances are around 8~10 cm
- Case sensor detection function
- Watchdog function secures system free from halting
- Provide different communication interface with controller.
- Special model to provides both T2 and Wiegand interface, it allow customer to use more flexible.(PXR-92ETW)
- Provide RS-485 communication interface, it may suit for long distance installation. (PXR-92ES)
- IP65 waterproof and dustproof testing, easy to install indoor and outdoor environments.
- Wide operation temperature range, it can be install in different arctic or tropical regions.


Ordering Information

Package Content:

- PXR-92 x 1
- Accessory Pack x 1
- Quick Start Guide x 1
- Plate x 1

Model No. Identification

P X R - 9 2 E T



Color

- Black (BL)

Specifications

Model No.	PXR-92ET	PXR-92EW	PXR-92ETW	PXR-92ES
Read Format	125 KHz (EM Compatible)			
Read Range	8-10 cm(max)			
Comm. Interface	T2	Wiegand	T2 / Wiegand	RS-485
Input Port	Case Sensor x 1			
ID Setting	NONE			DIP switch setting
Comm. Baudrate	NONE			19,200 bps-N-8-1
LED Indicator	Power / Comm.			
Beep Tone	Buzzer			
Ingress Protection	IP 65			
Power Input	DC 12V / 1A			
Current Consumption	200mA (max)			
Operating Temp.	-10°C~ 70°C / 14°F~ 158°F			
Relative Humidity	20% ~ 80%(Non-condensing)			
Dimension (LxWxH)(mm)	120 x 77 x 22			