

PXR-92MS(K)L Reader



Features

- Conforms to ISO 14443A, supporting MIFARE card.
- Unique ID or Block read format supported and programmable key value.
- Provides RS-485 communication interface for long distance installation
- Slim, stylish design, capacitive touch keypad with blue backlight . (PXR-92MSKL)
- Keypad function. When working with controller, it provides unlock modes including card-swiping, pressing card number by keypads or card-swiping with password to access (PXR-92MSKL)
- If the keypad function is disabled but under the entry mode of card-swiping with password, the keypad will be enabled automatically after swiping card and then disabled again after keypad operation. (PXR-92MSKL)
- Provides the doorbell design to connect the external doorbell (PXR-92MSKL)
- Auto-Learning function. 470 temporary cards' capacity to work as standalone operation mode
- IP65 rated ingress protection, suitable to install indoor and outdoor environments.
- Wide range of operating temperature to meet the requirements of tropical or frigid zone climate environment.
- Case sensor detection function to enhance the system security.
- Watchdog function secures system free from halting.

Ordering Information

Package Content:

- PXR-92 x 1
- Accessory Pack x 1
- Quick Start Guide x 1
- Plate x 1

Model No. Identification

P X R - 9 2 M S K L

- Auto Learning Keypad
- S: RS-485
- E: EM / M: MIFARE®
- Device Type
- Product Category

Color

- Black (BL)

Specifications

Model No.	PXR-92MSL	PXR-92MSKL
Read Format	Mifare (13.56 MHz)	
Read Range	3-5 cm(max)	
Comm. Interface	RS-485	
Keypad	None	13 Key (0-9, *, #, Doorbell)
Input Ports	3 Sensors (Door Sensor x 1 \ Exit Button x 1 \ Case Sensor x 1)	
Output Ports(Built-in)	Relay x 1 (Door Lock)	
Output Ports(External)	O.C. Output x 2 (Door Lock / Alarm, external ACU-30/90)	
ID Setting	DIP switch setting	
Comm. Baudrate	19,200 bps-N-8-1	
LED Indicator	Power / Comm.	
Beep Tone	Buzzer	
Ingress Protection	IP65	
Power Input	DC 12V / 1A	
Current Consumption	200mA (max)	
Operating Temp.	-10°C~ 70°C / 14°F~ 158°F	
Relative Humidity	20% ~ 80%(Non-condensing)	
Dimension (LxWxH)(mm)	120 x 77 x 22	